

Specification:

| Description | 5 Ton | 10 Ton | 20 Ton | 30 Ton | 50 Ton | 80 Ton | 100 Ton | 150 Ton | 200Ton | 250 Ton |
|-----------------------------|--------------|---------------|---------------|---------------|---------------|---------------|----------------|----------------|---------------|----------------|
| Crankshaft Diameter | 50 | 57 | 70 | 83 | 102 | 114 | 127 | 150 | 175 | 200 |
| Adjustment of Stroke | Jun-50 | Jun-60 | Nov-75 | 13-83 | 13-100 | 25-114 | 32-127 | 32-127 | 50.175 | 50-200 |
| Adjustment in Ram | 25 | 25 | 32 | 32 | 40 | 40 | 50 | 50 | 60 | 60 |
| Punch Hole in Ram | 25 | 25-Apr | 31-75 | 38-1 | 50-8 | 50-8 | 57 | 57 | 63-5 | 63-5 |
| Hole in Bed | 65 | 75 | 89 | 102 | 114 | 150 | 180 | 200 | 225 | 225 |
| Length & Width of Bed | 200x350 | 250x400 | 305x508 | 355x610 | 450x300 | 558x812 | 610x863 | 660x914 | 711x990 | 762x1066 |
| Thickness of Bed | 50 | 50 | 63 | 75 | 75 | 90 | 115 | 127 | 140 | 150 |
| Distance Between Bed to Ram | 180 | 228 | 300 | 355 | 400 | 450 | 507 | 558 | 610 | 711 |
| Stroke per Minute | 70 | 60 | 50 | 45 | 35 | 35 | 35 | 30 | 30 | 25 |
| H.P Required | 0.5 | 1 | 2 | 3 | 5 | 7.5 | 10 | 15 | 20 | 25 |
| Weight Approx | 350 | 550 | 1100 | 1400 | 2450 | 3850 | 4800 | 6000 | 8500 | 11500 |