

								Ram speeds (mm/sec)				Overall Dimension		
Tonnage MT	Bending capacity(in mm)(in MS UTS 45 kg / mm2) Y.S.25 kg / mm2)	Table size (in mm)	Clear Passing (in mm)	Ram stroke (in mm)	Open Height (in mm)	Close height (in mm)	Throat Depth (in mm)	Approach	Pressing	Return	Motor (KM) HP	Lenght (in mm)	Width (in mm)	Height (in mm)
20	1.62 X 1500	125 X 1500	1250	100	250	150	100	40	6	38	(2.2)3	1800	1500	1500
30	2 X 2000	125 X 2000	1700	100	280	180	200	30	7	30	(2.2)3	2250	1125	2500
40	2 X 2500	170 X 2500	2000	100	280	180	200	50	6	50	(3.75)5	2710	1280	3000
50	3 X 2000	170 X 2000	1500	100	280	180	200	48	6	48	(3.75)5	2250	1350	3400
50	2.5 X 2500 3.15 X 2500 (32 mm "V")	170 X 2500	2000	100	280	180	200	48	6	48	(3.75)5	2750	1350	3500
60	3.15 X 2500	170 X 2500	2000	150	330	180	200	36	5	36	(3.75)5	2750	1425	2725
80	4 X 2500	170 X 2500	2000	150	350	200	200	45	6	48	(5.5)7.5	2750	1600	5000
80	3.15 X 3000 4 X 2500	170 X 3000	2500	150	350	200	200	45	6	48	(5.5)7.5	3250	1600	5000
100	5 X 2500	170 X 2500	2000	150	350	200	200	38	5	38	(7.5)10	2800	1600	5200
100	4 X 3000 5 X 2500	170 X 3000	2500	150	350	200	200	38	5	38	(7.5)10	3300	1600	6000
125	5 X 3000 6 X 2500	220 X 3000	2500	150	350	200	300	30	5	60	(11.2)5	3300	1825	7000
125	6 X 2500 5 X 3000 4 X 4000	220 X 4000	3000	150	350	200	300	30	5	60	(11.5)5	4200	1825	8000
160	8 X 2500 6 X 3000	220 X 3000	2500	150	350	200	300	30	5	60	(15)20	3300	1875	8800
160	8 X 2500 6 X 3000 5 X 4000	220 X 4000	3000	150	350	200	300	30	5	60	(15)20	4200	1875	9800
200	8 X 3000 10 X 2500	220 X 3000	2500	200	410	210	300	20	5	50	(15)20	3300	1925	9500
200	10 X 2500 8 X 3000 6 X 4000	220 X 4000	3000	200	410	210	300	20	5	50	(15)20	4250	1925	10500
300	12 X 3000	300 X 3000	2500	200	410	210	300	19	5	30	(18.75)25	3275	2030	12000