

Technical Specification :

Model No.	Plate Width	Plate Thickness	Top Roll	Bottom Roll	Minimum Bending Diameter	Motor Power H.P.
VKPR 123	1250	3	100	90	250	2
VKPR 153	1500	3	115	100	290	3
VKPR 203	2000	3	130	105	325	3
VKPR 253	2500	3	150	125	375	5
VKPR 303	3000	3	175	150	450	7.5
VKPR 126	1250	6	125	105	315	3
VKPR 156	1500	6	140	115	350	5
VKPR 206	2000	6	160	135	400	5
VKPR 256	2500	6	175	150	450	7.5
VKPR 306	3000	6	200	170	500	10
VKPR 1210	1250	10	150	125	375	5
VKPR 1510	1500	10	160	135	400	7.5
VKPR 2010	2000	10	185	150	450	7.5
VKPR 2510	2500	10	200	170	500	10
VKPR 3010	3000	10	240	200	600	15
VKPR 1212	1250	12	175	140	450	7.5
VKPR 1512	1500	12	180	150	450	7.5
VKPR 2012	2000	12	205	160	525	10
VKPR 2512	2500	12	230	180	575	15
VKPR 3012	3000	12	260	220	650	20
VKPR 1216	1250	16	190	150	475	7.5
VKPR	1500	16	200	160	500	10

1516						
VKPR 2016	2000	16	215	175	550	12.5
VKPR 2516	2500	16	240	200	600	20
VKPR 3016	3000	16	275	225	700	20
VKPR 1220	1250	20	200	160	500	10
VKPR 1520	1500	20	215	170	550	12.5
VKPR 2020	2000	20	230	190	600	15
VKPR 2520	2500	20	260	215	750	20
VKPR 3020	3000	20	290	250	850	25
VKPR 1225	1250	25	240	200	750	15
VKPR 1525	1500	25	250	215	750	15
VKPR 2025	2000	25	275	230	850	20
VKPR 2525	2500	25	300	260	900	30
VKPR 3025	3000	25	340	290	1200	40
VKPR 2530	2500	30	375	325	1300	40
VKPR 3030	3000	30	400	350	1500	50
VKPR 2540	2500	40	400	350	1500	50
VKPR 3040	3000	40	430	380	2000	80

*All Dimensions are in mm