

Specification:

CAPACITY	10 TONS	20 TONS	30 TONS	50 TONS	80 TONS	100 TONS	150 TONS	200 TONS	250TONS
CRANK SHAFT DIA	57	75	82	100	115	125	150	175	200
BED SIZE- LR X FB	450x250	500x375	550x375	750x500	800x550	900x650	900x650	900x700	900x700
STROKE ADJUSTABLE	Jun-50	Jun-75	Jun-75	6-100	12-115	12-125	12-150	12-150	12-150
DEPTH OF THROAT	125	23-Jun	190	250	280	325	325	350	350
HOLE IN RAM	25	32	32	38	50	50	50	50	50
SHUT HEIGHT	200	200	225	250	288	325	300	350	350
SLIDE ADJUSTMENT	25	40	40	50	50	65	65	65	65
DIST BED TO RAM	250	275	300	350	400	450	450	500	500
HOLE IN BED	70	90	90	100	115	125	150	150	150
WHELL DIA	455	550	625	750	900	1000	1125	1175	1200
STROKES PER MINUTE	60	35	35	35	35	35	35	30	30
POWER REQUIRED	1/1440	2/1440	3/1440	5/1440	7.5/1440	10/1440	15/1440	20/1440	25/1440
APPROX WEIGHT	630	1200	1450	2600	3800	5500	7500	8500	9500

- Power Supply : 400/440 Volts, 3 Phase, 50 Cycles.
- All Dimensions Are In mm
- As Day to Day Improvements Are Contemplated We Reserve The Ring To Change Specification/Design Without Prior Notice
- Advice will be Solicited For Your Drawing.