

### Standard Accessories:

- Oil Pump
- Tool Box
- Slideway Cover
- Working Light

### Optional Accessories:

- 6" Vise
- Digital Readout
- Milling Chuck
- Mechanical Feed
- Power Feed
- Coolant Pump
- Clamp Kit
- Boring Head

### Mechanical Characteristics:

- High Quality, Tenacilous clay cast
- Taiwan Precise Leading screw
- High Quality Electrical Components
- Tempered, Quenched and Hardendend slideway
- High Precise Milling Head

### Standard or Economical Milling Machine Serials:

Model	Table size min	Travel	Spindle	Max distance between spindle & Table mm	Dimension mm	Net Weight Kgs	
	Longitude	Crossward	Vertical	Quill mm	Rotation	Taper	Motor

	(x) mm	(y) mm	(z) mm		Speed rpm		HP				
<b>3S/3E</b>	1270x2 54x82	890	395	400	127	80- 5440 (16Grad e)/60Hz	R8 (N T3 0)	3	4 0 5	1500x17 00x2100	1 2 8 0
<b>4S/4E</b>	1270x2 54x82	900	410	410	127		R8 (N T3 0)	3	4 7 0	1500x17 00x2100	1 4 5 0
<b>4SA/4E A</b>	1370x2 80x82	1000	420	430	127		R8 (N T3 0) (N T4 0)	3 5	4 1 0	1600x17 00x2200	1 6 5 0
<b>4SB/4E B/5SL</b>	1270x2 54x82	914	390	370	127		R8 (N T3 0)	4	4 2 5	1500x17 00x2100	1 5 0 0
<b>5S/5SA</b>	1370x3 05x85	910	420	420	127		R8 (N T4 0)	5	4 9 5 5 4 5	2000x15 00x2270	1 8 6 0
<b>5EA/5E B</b>	1370x2 80x85 1270x2 54x82	1000	390	406 370	127		R8 (N T4 0)	5	4 6 5 4 2 5	1600x17 00x2200	1 7 5 0